

Yeni
New
Новая

TEKNİK ÖZELLİKLER | **TECHNICAL SPECIFICATION** | **ТЕХНИЧЕСКИЕ ХАРАКТЕРИСТИКИ**

Standard ekipmanlar
Standard Equipments
Стандартное оборудование

Opsiyonel ekipmanlar
Optional Equipments
Дополнительное оборудование

		HKM 40	HKM 45	HKM 60	HKM 65 V	HKM 55	HKM 65	HKM 85	HKM 115	HKM 175
	DELİK ZİMBASI / PUNCHING / ПРОБИВКА ОТВЕРСТИЙ									
	Maksimum kalınlıkta çap Ø Diameterхmax. thickness Диаметр х макс. Толщину	Ø 20x15 mm	Ø 22x15 mm	Ø 28x15 mm	Ø 22x20 mm	Ø 20x20 mm	Ø 26x20 mm	Ø 33x20 mm	Ø 34x26 mm	Ø 40x32 mm
	Çap x kalınlık (xt) Diameterхthickness ДиаметрхТолщину	Ø 30x10 mm	Ø 38x8 mm	Ø 38x11 mm	-	Ø 40x10 mm	Ø 57x10 mm	Ø 57x12 mm	Ø 55x16 mm	Ø 57x22 mm
	Maksimum çapta kalınlık Maximum Diameter Максимальный Диаметр	Ø 38x8 mm	Ø 100x3 mm	Ø 110x3 mm	Ø 38x11 mm	Ø 100x3 mm	Ø 110x3 mm	Ø 110x4 mm	Ø 110x5 mm	Ø 125x5 mm
	İş kursu Stroke Ход	50 mm	50 mm	55 mm	40 mm	60 mm	55 mm	80 mm	80 mm	80 mm
	Kurs adedi (20 mm) Stroke count in (20 mm) Кол-во Ударов В (20мм)	x 20	x 20	x 25	(15mm) x 22	x 25	x 25	x 25	x 25	x 22
	Oluk derinliği Throat depth Глубина Зева	175 mm	175 mm	220 mm	240 mm	255 mm	305 mm	355 mm	355 mm	625 mm
Çalışma yüksekliği Working height Рабочая высота	970 mm	935 mm	955 mm	1050 mm	1030 mm	1030 mm	1080 mm	1110 mm	1130 mm	
	DOLU MALZEME MAKASI STEEL BAR SHEAR Резка круглого/квадратного прутка									
	Yuvarlak/dörtköşe Round/Square Круг/Квадрат	Ø 30- 25 mm	Ø 30- 25 mm	Ø 40- 35 mm	Ø 40- 38 mm	Ø 40- 40 mm	Ø 45- 45 mm	Ø 50- 50 mm	Ø 55- 50 mm	Ø 65- 55 mm
	KÖŞEBENT KESME MAKASI ANGLE SHEAR НОЖНИЦЫ ДЛЯ РЕЗКИ УГОЛКА									
	Dik köşebent (90°) Angle section (90°) Угловой Профиль (90°)	80x80x8 mm	100x100x10 mm	120x120x12 mm	100x100x10 mm	120x120x12 mm	120x120x12 mm	150x150x15 mm	150x150x16 mm	200x200x20 mm
	Açılı köşebent (45°) Angle section (45°) Угловой Профиль (45°)	50x6 mm	70x6 mm	80x8 mm	-	70x10 mm	70x10 mm	80x8 mm	80x10 mm	80x10 mm
	Çalışma yüksekliği Working height Рабочая высота	1110 mm	1140 mm	1155 mm	1070 mm	1130 mm	1140 mm	1200 mm	1215 mm	1130 mm
	SAC MAKAS (LAMA KESME) SHEET METAL SHEAR Гильотинные ножницы									
	Düz sac Sheet metal Листовой Металл	200x13 mm	200x15 mm	200x20 mm	350x15 mm	200x20 mm	300x20 mm	380x20 mm	380x25 mm	380x30 mm
	Düz sac Sheet metal Листовой Металл	300x6 mm	300x12 mm	300x15 mm	-	300x15 mm	375x15 mm	480x15 mm	600x15 mm	600x20 mm
	Bıçak uzunluğu Blade Length Длина Ножа	356 mm	316 mm	317 mm	352 mm	317 mm	380 mm	482 mm	610 mm	610 mm
	Köşebent açılı kesim tek kenar Angle shear one side Резка угла по одной стороне	80x10 mm	80x10 mm	80x10 mm	70x7 mm	80x15 mm	100x15 mm	120x15 mm	120x15 mm	120x15 mm
Çalışma yüksekliği Working height Рабочая Высота	980 mm	935 mm	955 mm	810 mm	900 mm	900 mm	940 mm	935 mm	810 mm	
	ÇENTİK AÇMA NOTCHING ВЫСЕЧЕННЫЕ НОЖНИЦЫ		HKM 45	HKM 60	HKM 65 V	HKM 55	HKM 65	HKM 85	HKM 115	HKM 175
	Malzeme kalınlığı Thickness Толщина		8 mm	10 mm	8 mm	10 mm	10 mm	13 mm	13 mm	16 mm
	Genişlik Width Ширина		35 mm	42 mm	50.8 mm	45 mm	45 mm	52 mm	60 mm	60 mm
	Derinlik Depth Глубина		75 mm	100 mm	90 mm	90 mm	90 mm	100 mm	100 mm	100 mm
Çalışma yüksekliği Working height Рабочая Высота		935 mm	955 mm	1060 mm	900 mm	900 mm	940 mm	935 mm	910 mm	
	ÖZEL KALIPLAR / OPTIONAL TOOLS / ДИСКРЕЦИОННЫЙ ИНСТРУМЕНТ	HKM 40	HKM 45	HKM 60	HKM 65 V	HKM 55	HKM 65	HKM 85	HKM 115	HKM 175
	U-I profil bıçakları (UPN - IPN kesmek için) U-I Section blades (for UPN - IPN cutting) U-I Образные Ножи	76x38 mm	80x45 mm	80x45 mm	100x50 mm	120x58 mm	120x58 mm	160x74 mm	200x90 mm	300x125 mm
	T profil bıçakları T Section Blades T Образные Ножи	38x6 mm	40x5 mm	80x9 mm	-	80x9 mm	90x11 mm	100x11 mm	120x13 mm	150x15 mm
	Özel çentik takımı Special V-Notching tooling Специальный V-образный инструмент		100x100x8 mm	100x100x10 mm	90x90x8 mm	100x100x10 mm	100x100x10 mm	100x100x13 mm	100x100x13 mm	100x100x16 mm
	V kıvrıma V - bending Press Brake V - Образный Гибочный Пресс		100x12 mm	100x12 mm	160x8 mm	250x12 mm	250x15 mm	250x20 mm	250x22 mm	250x25 mm
		Lama kıvrıma maksimum Bar bend Max. Гибка Прутка Макс.				250x6 mm	500x3 mm	500x3 mm	500x4 mm	700x3 mm
	Sac kıvrıma maksimum Sheet bend. max. Гибка Листа Макс.									
	Çentik kısmında zimba Punching on notcher Пробивка на высечке		85 mm	110 mm	-	125 mm	125 mm	125 mm	125 mm	125 mm
		Sac kıvrıma maksimum Max. capacity Макс. Возможность		Ø 18x12 mm	Ø 20x12 mm	-	Ø 38 x8 mm	Ø 38 x8 mm	Ø 38 x10 mm	Ø 38 x12 mm
	TEKNİK ÖZELLİKLER TECHNICAL DATA / ТЕХНИЧЕСКИЕ ХАРАКТЕРИСТИКИ	HKM 40	HKM 45	HKM 60	HKM 65 V	HKM 55	HKM 65	HKM 85	HKM 115	HKM 175
	Motor gücü Motor Power Мощность Двигателя	3 kW	4 kW	4kW	5.5 kW	5.5 kW	5.5 kW	7.5 kW	11 kW	11 kW
	Ağırlık Weight Вес	580 kg	1165 kg	1440 kg	1215 kg	1520 kg	1600 kg	2315 kg	2920 kg	6000 kg
	Makina ölçüleri (UxGxY) Machine Dimensions (LxWxH) Габариты (ДxШxВ)	1100x800x1520 mm	1430x950x1680 mm	1520x950x1780 mm	1180x900x1720 mm	1600x950x1880 mm	1700x950x1880 mm	1920x950x2040 mm	2040x950x2180 mm	2730x1150x2280 mm
	Basınç Power (Pressure) Усилие	40 ton	45 ton	60 ton	65 ton	55 ton	65 ton	85 ton	115 ton	175 ton